



PRODUCT DATA SHEET

Premium Quality Lubricants

FLEETPRO™ ULTRA 5W-40 SYNTHETIC ENGINE OIL ALL SEASON HIGH PERFORMANCE DIESEL ENGINE OIL

PRODUCT DESCRIPTION

FLEETPRO™ FULL SYNTHETIC heavy duty diesel engine oil is formulated with advanced additive technology and Synthetic base stocks. This oil exceeds the performance requirements of API CJ-4 for model year 2007 and newer diesel engines. It outperform conventional SAE 15W-40 API CJ-4 oils in Fuel Economy, Wear Protection, All Season performance, Extended Drain Interval and Reduced Oil Consumption.

INDUSTRY AND OEM SPECIFICATIONS

- * API CJ-4/CI-4 Plus/CI-4 and CH-4
- * API SM
- * Renault RLD-3
- * Mack EO-O Premium Plus 07/03/PP
- * Cummins CES 20081
- * Volvo VDS 4/3 and 2
- * Mercedes-Benz p228.3, p228.31
- * CAT ECF-3/2
- * Detroit Diesel 93K218, 93K215, 93K214
- * ACEA E7-04
- * Man
- * JASO DH-2
- * Global DHD-2
- * MTU Type I and Type II

APPLICATIONS

FLEETPRO™ FULL SYNTHETIC SAE 5W-40 motor oil is recommended for heavy duty diesel and mixed fleets in all types of over the road service. It is an excellent choice for use in diesel powered equipment provided by Caterpillar, Cummins, John Deere, Detroit Diesel, Mack, Mercedes-Benz, International and Volvo engine in all types of service.

TYPICAL PROPERTIES

SAE GRADE	TEST	5W40
Viscosity @100°C	D445	14.3
Viscosity Index	D2770	169
CCS Viscosity @-30°C (cP max.)	D5293	6300
Pour Point °C	D97	-35
TBN	D2896	8

PN2009JUN